

NOVELTY GOLF PUTTER

BACKGROUND OF THE INVENTION

Field of the Invention

This invention relates to the game of golf and more particularly, to a novelty golf club.

Summary of the Prior Art

In golf, it is the well known objective of the game to move a golf ball from a starting point (the tee) to a finishing point (the hole) in the fewest strokes possible over a course having a number of holes, such as nine or eighteen. The hole is generally positioned at an arbitrary location on a smooth area of grass or green. An appropriate golf club known as a putter is normally used on the green to move the ball into the hole. It is a common courtesy during a golf game for an opposing player(s) to concede a putt without putting it in the hole, if a ball is sufficiently close. One arbitrary gauge of conceding a putt occurs when the distance between the ball lying on the green and the hole is within "the leather" or the length of the putter handle.

SUMMARY OF THE INVENTION

It is an objective of the invention to provide a novelty putter which may function as a normal putter, but also is capable of being a novelty club by which the concept of being within the leather for concession of a putt is extended to the advantage of the player putting. The handle of a putter herein is normally secured in a conventional manner to the club shaft. The handle is also removable from the shaft and remains in retention to the shaft through an elongated line or strap to extend the length of the handle area with respect to the club shaft and thus extend the distance from the hole at which a putt is conceded.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a side elevational view of a first embodiment of the novelty golf putter of the invention;

Fig. 2 is a side elevational view of the novelty golf putter of Fig. 1 with its handle removed;

Fig. 3 is a side elevational view of a second embodiment of the novelty golf putter of the invention; and

Fig. 4 is a partial side view, with parts removed, of the shaft and inner rod of the novelty golf putter of Fig. 3.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, there is illustrated the novelty golf putter of the invention, generally designated by reference numeral 2. The putter 2 includes a typical metal club head 4 and an elongated hollow shaft 6 formed from metal or other suitable material. The bottom end 8 of the hollow shaft 6 is suitably affixed in a hole (not shown) within the top of the metal removable club head 4. The upper end portion 10 of the shaft 6 is affixed to a hollow cylindrical handle 12 by external threads 14 on shaft 6 and internal threads (not shown) provided at an internal position within the open bottom end 16 of handle 12. The handle 12 creates an upper gripping area formed of a leather or rubber material suitably wrapped around the shaft 6. The end of shaft 6 may extend partially or substantially into the handle 12 dependent on the position of the internal threads (not shown) of the handle 12. Alternatively, the hollow cylindrical handle 12 may be affixed to the shaft 6 by detents or other locking elements (not shown) that lock the handle 12

1 on the shaft 6 for normal play and allow removal of the handle 12 to extend the length of the
2 handle within the contemplation of the invention. An elongated line or strap 20 (Fig. 2) formed
3 from a plastic line, leather strap, wire and the like is suitably affixed within the handle 12 at one
4 end portion (not shown) and within the hollow shaft 6 at the opposite end portion of the line or
5 strap 20 (not shown) to secure the shaft 6 to the handle 12 when the handle is removed as in Fig.
6 2. The line or strap 20 is stowed within the shaft 6 when the handle 12 is in its secured portion of
7 Fig. 1. During play, the player using putter 2 may at his or her option claim that the ball is within
8 the leather by removing handle 12 and stretching the line 20 to greatly increase the distance from
9 the hole at which a putt is conceded.

10 Referring now to Figs. 3 and 4, there is illustrated a second embodiment of the novelty
11 golf putter of the invention; generally designated by reference numeral 2'. The putter 2' includes a
12 putter head 4', and a hollow shaft 6' attached to the putter head 4' in hole 8'. A handle 12' having
13 complimentary internal threads (not shown) is attached to the threads 10' of shaft 6' for normal
14 putting. A rod 20a is telescopically mounted within shaft 6' in stowed relationship in attachment
15 to handle 12' by screws and the like (not shown) to allow the handle 12' to be extended outward
16 relative to shaft 6' in accordance with the invention. To prevent detachment of the handle 12'
17 from the shaft 6', the lower end of shaft 6' includes an enlarged end 32 to engage the shoulder 30
18 to prevent further movement of the rod 20a. The handle 12' is unscrewed from the shaft 6' to
19 permit extension of the rod 20a and handle 12'. After being extended, the rod 20a can be
20 reinserted into the shaft 6' and the handle can be reattached to threads 10'.